# **Prosper:** A Framework for Extending Prolog Applications with a Web Interface

http://prospear.sourceforge.net/

### Levente Hunyadi

Budapest University of Technology and Economics

extension infrastructure Prolog Server Pages core document • imports server page documents from repository • converts documents into intermediate term repository predefined special elements representation server page evaluates documents conditional evaluation documents within • generates output iteration, retrieving more solutions expression language web server root assignment to local page variables extension to is/2 predicate inserting values of expressions in output typed expressions access to context data extensible with custom functions user-defined elements logic module • defined by transformation rules (prerepository processing-time and evaluation-time) context module conventional Prolog • no restrictions compared to predefined • asserts request-specific conmodules in a elements text as dynamic predicates dedicated directory; loads and saves persistent these are referenced context (sessions) by server page



### Process of reply generation

## Server page documents



a syntax-verified representation

### evaluation unbound variables

in intermediate

evaluated

term

term representation are instantiated based on context depends on context that derives from HTTP request

#### content generation

output document most commonly (X)HTML

tiation and their scope is limited to descendant elements.

<psp:for-each-else>

<psp:for-each function="queens(N)" iterator="L"> Solution:

<board:chessboard size="{ N} " figures="L" />

- </psp:for-each>
- <psp:else>
- Sorry but there are no solutions.

</psp:else> 13

- </psp:for-each-else> 14
- 15 </psp:assign> 16 </html>

6

8

9

10

11

12

#### Line 7

Iteration constructs are ideal to display repetitive content. The term in the attribute *function* is extended with an extra output argument when called. The local variable *L* gives access to the output argument.

Line 5 (right) Fetch the value of the HTTP GET context variable *n* and converts it into a number. Expression language terms like this are enclosed in {curly braces}.



**Budapest University of Technology and Economics**